

Admitex BONUS 524

PLASTICIZER

CHARACTERISTICS

ADMITEK BONUS 524 is a plasticizing additive intended for ready-mixed concrete. The additive was created on the basis of new generation of polycarboxylates, thanks to which it can be used for wide range of dosages and enables:

- plasticizing or large liquidation of concrete mix,
- transport of concrete mix at long distances, i.e. long maintenance of consistency of concrete mix in time,
- production of concrete mix of large cohesiveness,

USAGE

- for ready-mixed and BWV high-value concrete,
- for all types of cements

DOSAGE

Dosage from 0.3% to 1.5% of the cement mass. Recommended dosage 0.6-1.0 % to the cement mass. The optimum dosage of the additive should be defined on the basis of sample batches. Time of mixing should be defined on the basis of performance of sample batches. By secondary dosage on site to concrete mixers, the recommended time of mixing is 1 min/ 1m³.

TECHNICAL DATA

Colour: brown

Density: 1.08 pH: 5 - 6

Content of chlorides <0.10%



Admitex BONUS 524

PLASTICIZER

STORAGE

Store in roofed rooms, in tightly closed packages in the temperature from 5 to 40°C. Stir after long storage or freezing. Date of expiry 12 months.

PACKAGING AND TRANSPORT

- in 1000 or 200-liter return plastic packages,
- transport in locked means of transport, not subject to ADR limitations,
- the additive is a safe product,

SAFETY PRECAUTIONS

ADMITEK BONUS 524 is not a hazardous material. Handle in accordance with the assumed rules of safety. In case of getting dirty take off clothes and cleanse dirty skin with a large amount of water.

Detail information regarding health, safety available in the Characteristics Sheet.

EMARKS

Data included in Information Sheet is of approximate nature and was presented on the basis of experience in production and practical use. Due to different use of raw materials by production of concrete one should perform appropriate tests and examinations. The guarantee of quality comprises only sale and delivery of the product and does not comprise the method of product storage by the client.

In case of any further questions please contact us under the following telephone number: +48 32 60124 79

