

Admitex **BONUS 600**

PLASTICIZER

CHARACTERISTICS

ADMITEX BONUS 600 is an additive created on the basis of polycarboxylate esters, which assures reduction of batch water at the level that enables production of reologically stable mixes and guarantees repeatability of concrete resistance results. Wide range of dosage allows optimum use in many types of produced concrete.

Thanks to using the **BONUS 600** additive one can achieve:

- increase liquidity/consistency of the concrete mix,
- increase initial and final resistance,
- improve pumpability and building-in of the concrete mix.

USAGE

- for ready-mixed and precast concrete,
- BWB and self-consolidating (SCC) high-value concrete
- reinforced and pre-stressed concrete,
- for all types of cements

DOSAGE

Dosage from 0.3% to 2.0% of the cement mass. Recommended dosage 0.8-1.2% to the cement mass. The optimum dosage of the additive should be defined on the basis of sample batches. Time of mixing should be defined on the basis of performance of sample batches. By secondary dosage on site to concrete mixers, the recommended time of mixing is 1 min/ 1m³.

TECHNICAL DATA

Color: brown Density: 1.08 ±0.02 pH: <7



Admitex *BONUS 600*

PLASTICIZER

Content of chlorides <0.10%

STORAGE

Store in roofed rooms, in tightly closed packages in the temperature from 5 to 40°C. Stir after long storage or freezing. Date of expiry 12 months.

PACKAGING AND TRANSPORT

- in 1000-liter return containers,
- in 200-liter return plastic barrels,
- transport in locked means of transport, not subject to ADR limitations,

SAFETY PRECAUTIONS

ADMITEX BONUS 600 is not a hazardous material. Handle in accordance with the assumed rules of safety. In case of getting dirty take off clothes and cleanse dirty skin with a large amount of water.

Detail information regarding health, safety available in the Characteristics Sheet.

EMARKS

Data included in Information Sheet is of approximate nature and was presented on the basis of experience in production and practical use. Due to different use of raw materials by production of concrete one should perform appropriate tests and examinations. The guarantee of quality comprises only sale and delivery of the product and does not comprise the method of product storage by the client.

In case of any further questions please contact us under the following telephone number: +48 32 60124 79

