

Admitex *HIGRO 210*

PLASTICIZING AND SEALING ADDITIVE

CHARACTERISTICS

ADMITEX HIGRO 210 is a plasticizing and hydrophobizing additive, staining the colour of hardened concrete, intended for concrete mixes of humid consistency. The additive strongly binds water in the concrete mix without losing the size of the products, additionally improving its proper placement and thickening in the form. The additive improves resistance, durability of the ready product in conditions of low temperatures.

USAGE

- for vibropressed concrete of the surface layer,
- for vibrated concrete of humid consistency,
- for all types of cements.

DOSAGE

Dosage from 0.5% to 1.2% of the cement mass. Recommended dosage 0.6-0.8% to the cement mass. The optimum amount of the additive should be defined on the basis of performed technological tests. The time of mixing necessary to receive homogeneous mix should be defined on the basis of performed technological tests.

TECHNICAL DATA

Colour: white matt

Density: 1.0 pH: 6 - 8

Content of chlorides <0.10%



Admitex *HIGRO 210*

PLASTICIZING AND SEALING ADDITIVE

STORAGE

Store in roofed rooms, in tightly closed packages in the temperature from 5 to 40°C. Stir after long storage. Do not allow the additive to freeze. Date of expiry 12 months.

PACKAGING AND TRANSPORT

- in 1000 or 200-liter return plastic packages,
- transport in locked means of transport, not subject to ADR limitations,
- the additive is a safe product,

SAFETY PRECAUTIONS

ADMITEK HIGRO 210 is not a hazardous material. Handle in accordance with the assumed rules of safety. In case of getting dirty take off clothes and cleanse dirty skin with a large amount of water. Detail information regarding health and safety is available in the Characteristics Sheet.

REMARKS

Data included in Information Sheet is of approximate nature and was presented on the basis of experience in production and practical use. Due to different use of raw materials by production of concrete one should perform appropriate tests and examinations. The guarantee of quality comprises only sale and delivery of the product and does not comprise the method of product storage by the client. In case of any further questions please contact us under the following telephone number: **+48 32 60124 79**

