

# Admitex LP 0.6

## ADDITIVE TO VIBROPRESSED PRODUCTS

### CHARACTERISTICS

**ADMITEX LP 0.6** is an additive that has strong dispersing effect on the cement grains in moist concrete mixes. The mechanism of water retention allows regulation in wider scope of the amount of batch water in the concrete mix thus eliminating the effect of the so-called barrels. The advantage of such solution is to improve hydration of cement, compaction and resistance of concrete.

### USAGE

- for road products: sett, curbs
- for textural and constructional layers of vibropressed concrete,
- for products of small architecture: palisades, pots etc.,

### DOSAGE

The additive should be added in the scope of 0.2 - 0.5% of bond mass and is dependent on the assumed technical requirements. Dose together with batch water. The time of mixing should be precisely defined.

### TECHNICAL DATA

Base: modified surfactants/polymers

Colour: colourless

Density: 1.000±0.02

pH: 8 ±-10

### STORAGE

Store in roofed rooms, in tightly closed packages in the temperature from 5 to 40°C. Stir after long storage or freezing. The product is non-flammable. The date of expiry is 12 months.



# **Admitex** LP 0.6

## **ADDITIVE TO VIBROPRESSED PRODUCTS**

### **PACKAGING AND TRANSPORT**

- in 1000-liter return containers,
- in 200-liter return plastic barrels,,
- transport in locked means of transport, not subject to ADR limitations,
- the additive is practically a non-hazardous product,

### **SAFETY PRECAUTIONS**

ADMITEX LP 0.6 is not a hazardous material. Handle in accordance with the assumed rules of safety. Avoid contact with eyes, mucosa and skin. In case of getting dirty take off clothes and cleanse dirty skin with a large amount of water. Detail information regarding health, safety is available in the Characteristics Sheet.

### **REMARKS**

Data included in Information Sheet is of approximate nature and was presented on the basis of experience in production and practical use. Due to different use of raw materials by production of concrete one should perform appropriate tests and examinations. The guarantee of quality comprises only sale and delivery of the product and does not comprise the method of product storage by the client.

In case of any further questions please contact us under the following telephone number: **32 601 24 79**

