

Admitex LP 0.4

ADDITIVE TO VIBROPRESSED PRODUCTS

CHARACTERISTICS

ADMITEX LP 0.4 is an additive intended for vibropressed concrete and moist concrete that enables better compaction of the concrete mix, simultaneously increasing the mechanical durability of the received product.

Even by minimum dosage one can:

- decrease the amount of used cement,
- increase the initial and final resistance,
- increase production efficiency,
- improve appearance - sharper edges, more compact surface,
- increase tightness, water absorption and frost resistance,
- decrease tendency to occurrence of efflorescence,
- increase intensiveness of the colour.

USAGE

- for textural layers of vibropressed concrete,
- for products of small architecture: palisades, pots etc.,
- for road products: sett, curbs

DOSAGE

The additive should be added in the scope of 0.2 - 0.6% of bond mass and is dependant on the assumed technical requirements. Dose together with batch water. The time of mixing should be precisely defined.



Admitex LP 0.4

ADDITIVE TO VIBROPRESSED PRODUCTS

TECHNICAL DATA

Base: surfactants

Colour: green-blue

Density: 1.007 ±0.02

pH: 7±1

STORAGE

Store in roofed rooms, in tightly closed packages in the temperature from 5 to 40°C. Store after long storage or freezing. Date of expiry 12 months.

PACKAGING AND TRANSPORT

- in 1000-liter return containers,
- in 200-liter return plastic barrels,
- transport in locked means of transport, not subject to ADR limitations,
- the additive is a safe product,



Admitex LP 0.4

ADDITIVE TO VIBROPRESSED PRODUCTS

SAFETY PRECAUTIONS

ADMITEK LP 0.4 is not a hazardous material. Handle in accordance with the assumed rules of safety. Avoid contact with eyes, mucosa and skin. In case of getting dirty take off clothes and cleanse dirty skin with a large amount of water.

Detail information regarding health, safety available in the Characteristics Sheet.

REMARKS

Data included in Information Sheet is of approximate nature and was presented on the basis of experience in production and practical use. Due to different use of raw materials by production of concrete one should perform appropriate tests and examinations. The guarantee of quality comprises only sale and delivery of the product and does not comprise the method of product storage by the client.

In case of any further questions please contact us under the following telephone number: **32 60124 79**

