

# **Admitex** **NANOX-C2**

## **AGENT FOR CONCRETE IMPREGNATION**

### **CHARACTERISTICS**

**ADMITEX NANOX C2** nanoimpregnate intended for deep and surface hydrophobic and oleophobic protection of every kind of natural stone and other mineral unglazed surfaces inside or outside of objects. It penetrates well deep in the structure - it is resistant to abrasion, it does not polish, it does not tarnish, and it does not change the color.

### **USAGE**

- for mineral surfaces like clinker,
- face tiles,
- sett, sidewalk plates,
- all-natural stones such as marble, granite, sandstone
- for all types of concrete surfaces.

### **METHOD OF USE**

**ADMITEX NANOX C2** - shake before use, do not dilute, apply in two stages. First abundant application on clean and dry surface so that the impregnated surface changed its color to darker for several seconds. Second application after 30 minutes only on surface, spreading on surface excess of impregnate, especially drops. Leave for cross-linking for 4-6 hours, protecting at this time against direct contact with water. Full protection of the surface is obtained after 24 hours. The use of NANOX C2 preparation is dependant on the structure of the material and the method of application, the average is 8-10 m<sup>2</sup> from 1 liter of the product.



# **Admitex** **NANOX-C2**

**AGENT FOR CONCRETE IMPREGNATION**

## **TECHNICAL DATA**

Colour: milk-white

Density: ~1 g/cm<sup>3</sup> in 20°C

pH: 6 ±7

## **STORAGE**

Store in roofed rooms, in tightly closed packages in the temperature from 5 to 20°C. Protect from freezing or overheat. Stir before use. Date of expiry 12 months.

## **SAFETY PRECAUTIONS**

**ADMITEK NANOX C2** must not be consumed, inhaled. It is biodegradable, and one should protect eyes while using it. While spreading, use personal protective equipment: masks, gloves and protective glasses. Utilize in accordance with effective regulations, do not remove with residential garbage, do not pour into sewerage. Detail information regarding health, safety is available in the Characteristics Sheet.

## **REMARKS**

Data included in Information Sheet is of approximate nature and was presented on the basis of experience in production and practical use. Due to different use of raw materials by production of concrete one should perform appropriate tests and examinations. The guarantee of quality comprises only sale and delivery of the product and does not comprise the method of product storage by the client.

In case of any further questions please contact us under the following telephone number: 32 601 24 79

